

falcon™ X3



New

HAND HELD/PISTOL GRIP

Datalogic **Power³ HIGHLIGHTS**

Ultimate Performance!

> REAL TIME DATA CAPTURE

- > Capture with a high performance laser scanner with Green Spot, an auto ranging laser (XLR) scanner, or a 2D imager with Green Spot combined with a 3 mega pixel color camera
- > Communicate over a Summit 802.11 a/b/g radio with CCX v4 certification for security and seamless roaming or through wired standards including USB, RS232, modem and Ethernet
- > Parallel computer architecture combines a PXA 310 and Cortex-M3 processors with a base memory package of 256 MB RAM / 256 MB Flash and choice of Microsoft Windows operating systems: Windows Mobile or CE

> ERGONOMIC & RUGGED

- > Ergonomic hand held and pistol grip form factors balance a 3.5 inch display, full keyboards and a one piece 5,000 mAh battery
- > Functional rubberized plastic enclosures survive daily abuse and trauma from drops to concrete and exposure to water and dust
- > Users feel the full shift difference of oversized numeric and alphanumeric back lit keyboards, a crystal clear display and an arched pistol grip handle with ergonomic trigger

> EASY & INTUITIVE

- > Develop using the Datalogic Mobile industry leading software development kit for the ultimate in device control
- > Deploy quickly with Datalogic Utilities, Scan to Configure and Wavelink® Terminal Emulation
- > Direct the installation, maintenance and management using Wavelink® Avalanche console for the site or enterprise

FEATURES

- > Datalogic's trademark ergonomics balance a 3.5" display and full shift battery
- > Ruggedized with 1.8 m (6 ft) drop to concrete resistance and IP64 protection class
- > High performance laser with Green Spot
- > Wide aspect 2D imager with Green Spot
- > Auto Ranging Laser
- > Optional 3Mpixel autofocus camera
- > CCX v4 certified 802.11 a/b/g radio
- > Bluetooth® wireless communications
- > Microsoft Windows Mobile 6.5 or Windows CE 6.0 operating system
- > Parallel processor architecture combines an XScale™ PXA 310 and a Cortex-M3 processor
- > 256 MB RAM / 256 MB Flash memory
- > User-accessible MicroSD memory slot
- > Wavelink® Avalanche® device management and Terminal Emulation prelicensed
- > Datalogic Utilities and Software Development Kit
- > Pal Application Library prelicensed

APPLICATIONS

- > **Warehouse and Distribution Centers** - Retail, Wholesale, Manufacturing, Automotive/Industrial, Electronics, Food/Beverage, Consumer Products, Pharmaceutical, Third Party Logistics (3PL)
 - > Receiving
 - > Cross docking
 - > Put Away
 - > Staging
 - > Voice picking
 - > Shipping
 - > Cycle Count
 - > Inventory
 - > Shelf replenishment
 - > Price management
 - > Order entry
 - > Assisted sales
 - > Planogram verification
 - > Damaged goods documentation



SPECIFICATIONS



> PHYSICAL CHARACTERISTICS

DIMENSIONS	Hand held: 225 x 88 x 55 mm, 64 x 40 mm at keyboard (8.9 x 3.5 x 2.2 in, 2.5 x 1.6 in) Pistol grip: 225 x 88 x 168 mm (8.9 x 3.5 x 6.6 in)
WEIGHT	Hand held: 626 g (22.1 oz) Pistol grip: 699 g (24.6 oz)
DISPLAY	Transflective TFT daylight readable color display, 240 x 320 pixels, 3.5 inch diagonal, 64K colors, 200 nit backlight, touch screen
AUDIO KEYBOARD	Loudspeaker; Microphone Polycarbonate hard cap keyboards with backlight 29 key numeric or 52 key alpha numeric with discrete navigation
OPERATING TEMPERATURE	-20°C to 50°C (-4°F to 122°F)
STORAGE TEMPERATURE	-40°C to +70°C (-40°F to 158°F)
DROP RESISTANCE	Withstands 18 drops from 1.8 m (6 ft) onto concrete
ENVIRONMENTAL SEALING	IP64 standard for water and dust resistance

> SYSTEM

OPERATING SYSTEM	Microsoft Windows CE 6.0 with Microsoft WordPad and Internet Explorer 6.0 Microsoft Windows Mobile 6.5 with Mobile tools: Outlook Mobile, Word Mobile, Excel Mobile, PowerPoint Mobile, One Note Mobile and Internet Explorer Mobile 6.0 XScale™ PXA310 @ 624 MHz Cortex-M3, 32 bit @ 72 MHz
MICROPROCESSOR	256 MB
COPROCESSOR	256 MB
SYSTEM RAM MEMORY	MicroSD card slot compatible with SDHC cards, user-accessible
SYSTEM FLASH MEMORY	Time and date stamping under software control
EXPANSION SLOTS	Removable battery pack with rechargeable Li-ion batteries; 3.7 V 5000 mAh (18.5 Watt hours)
REAL-TIME CLOCK	
POWER SUPPLY	

> COMMUNICATION

INTERFACES	Main connector with USB Host, USB Client, RS232 up to 115.2 Kbps, and audio headset support
LOCAL AREA NETWORK (LAN)	Summit IEEE 802.11 a/b/g Frequency range: Country dependent, typically 2.4 GHz and 5.2 GHz
PERSONAL AREA NETWORK (PAN)	Cisco Compatible CCX v4 Security Bluetooth® Wireless Technology IEEE 802.15 Class 2 with EDR

> CAPTURE

LASER CHARACTERISTICS	High Performance Laser (HPL) with Green Spot, Auto Ranging Laser (XLR) 40 ± 6 scan/sec 0.20 mm / 7.5 mils HPL: 7 - 91 cm (3 - 36 inches) depending on bar code density XLR: Non reflective labels from 18 - 393 cm (7 to 154 in) depending on bar code density; Reflective labels to 1376 cm (542 in) All ranges dependent bar code size and density. Near range on reflective bar codes determined by degree of reflectivity and width of bar code
SCANNING RATE	GS1 Databar, EAN/UPC, Code 39, Code 32, 2/5 Codes, Codabar, Code 128, EAN128, MSI, Code 93
MINIMUM RESOLUTION	VLD - Class 2/II EN 60825-1/CDHR
DEPTH OF FIELD	
BAR CODES	
LASER CLASSIFICATION	
IMAGER CHARACTERISTICS	Wide Aspect Imager with Green Spot 60 frames/sec maximum Linear codes at 4 mils; 2D codes at 5 mils 5 to 40 cm (2 to 16 in), depending on bar code size and density
SCANNING RATE	PDF417, Micro PDF, Datamatrix, QR Code, Micro QR, Maxicode, Aztec, Postnet, Planet, Japan Post, Aztec, Australia Post, KIX Code, Royal Mail, Intelligent Mail and UPU FICS, GS1 Databar, EAN/UPC, Code 32, Code 39, 2/5 Codes, Codabar, Code 128, EAN128, MSI, Code 93, ISBT 128, Bookland EAN and ISSN EAN
MINIMUM RESOLUTION	CDRH/IEC Class II
DEPTH OF FIELD	IEC Class 1M
BAR CODES	
LASER CLASSIFICATION	
LED CLASSIFICATION	
CAMERA CHARACTERISTICS	3 Mega pixel color with autofocus and LED flash
IMAGE FORMATS	BMP, JPEG

> SOFTWARE

DEVELOPMENT	Datalogic Windows SDK™ Wavelink® Studio™ MCL-Collection™ Java Virtual Machine
TERMINAL EMULATION	Wavelink® Industrial Browser™ Wavelink® Terminal Emulation™ prelicensed
CONFIGURATION & MAINTENANCE	Wavelink Avalanche® MC prelicensed Wavelink Avalanche® SE prelicensed Avalanche Remote Control™ Datalogic Firmware Utility Datalogic Desktop Utility Datalogic Configuration Utility
SECURITY	Wavelink CE Secure Wavelink Certificate Manager
APPLICATIONS	Vo-CE™ (voice recognition) Wavelink® Communicator (push to talk) Wavelink® SpeakEasy (voice recognition) Pal Application Library prelicensed

ACCESSORIES



Caution: Laser Radiation - do not stare into beam



Single Slot Dock with Spare Battery Slot
(Opt. Ethernet or Modem Connection)



Four Slot Dock
(Optional Ethernet Connection)



Multi Battery Charger



Soft case and Holster

Specifications are subject to change. Please check www.mobile.datalogic.com for the latest product specifications. For information on product use limitations, please refer to the user manual available at www.mobile.datalogic.com/manual