

# SR61Bex

Rugged Bluetooth®  
Handheld Scanner



- **Highly versatile scanning with integrated near-far area imaging technology**
- **Omni-directional scanning increases productivity**
- **Ready for the increased use of 2D and stacked symbologies**
- **Interfaces with Intermec terminals and personal computers**
- **Easy configuration and personalization**
- **Industrial durability stands up to harsh environments**

The Intermec SR61Bex is the only handheld scanner on the market with integrated near/far area imaging technology, offering customers the unparalleled flexibility to read multiple symbologies, omni-directionally at distances of 6 inches to over 50 feet. It incorporates rugged design with Bluetooth® wireless communication.

The SR61Bex eliminates the need for multiple scanners and substantially reduces total cost of ownership. With the SR61Bex, users can scan 1D, 2D, composite and postal codes; capture images, signatures and documents; read at near and far distances; and successfully cope with damaged, poorly printed or partially obscured codes in variable lighting conditions.

In addition, the cordless SR61Bex features a personal area network (PAN) radio based on Bluetooth® communication protocol, making scanning easier and safer with no costly cables to damage or become entangled. Users gain mobility up to 100 feet from the host and can connect up to seven SR61Bex scanners to one Intermec host device.

Operators of fork trucks equipped with an Intermec vehicle-mounted mobile computer such as the CV30 or CV60, will appreciate how the near/far scanning capability of

the SR61Bex allows them to seamlessly transition between scanning objects held in their hand to scanning pallets located more than 50 feet away, a common requirement in warehouse management applications.

With omni-directional scanning, laser pointer auto-determining illumination and centered decoding, the SR61Bex makes it easy to scan at variable distances, lighting conditions and angles, improving worker productivity and accuracy.

The SR61Bex is ideal for inventory management, picking, shipping and receiving, cross docking, work-in-process, tool crib, and pallet tracking scanning applications.

The SR61Bex includes Intermec's EasySet™ software setup tool for easy configuration and personalization to meet the specific needs of the user's environment, whether that includes reading specific barcode symbologies, decoding poor quality or damaged barcodes or utilizing image capture for proof of delivery and point of service applications. Users can also quickly set security options, select beeper tones and volumes, specify good read and error read responses, and make many other customizations.

Built to withstand demanding application environments, the SR61Bex survives multiple drops to concrete, hot and cold temperatures, and is sealed against dirt and water. The cordless SR61Bex delivers 10+ hours of use with a long lasting lithium ion battery that can be easily swapped ensuring minimal downtime.

The SR61Bex enables companies to more effectively address their current data capture needs while providing built-in readiness for tomorrow's new warehouse management requirements.

#### Physical Characteristics

**Length:** 17.78 cm (7 in)  
**Width:** 6.99 cm (2.75 in)  
**Depth:** 11.43 cm (4.5 in)  
**Weight (with battery):** 425 gm (15 oz)

#### Power

**Battery Type:** Lithium-ion  
**Battery Life:** 10+ hours per full charge  
**Recharging Time:** 2.5 hours for 90% charge

#### Connectivity

Bluetooth radio connection to Intermec computers including the CN3 series, CK3, CK30, CK31, CK32, CK60, CK61, CV30, CV60, 700 series and standard PCs.

#### Radio Characteristics

**Frequency Band:** 2.4 Ghz  
**Radio Type:** Bluetooth Class 1 version 1.2  
**Radio Data Rate:** 1 megabit per second

#### Radio Range

**Host radio Class 1:** 30.5 m (100 ft)  
**Host radio Class 2:** 10 m (32.8 ft)  
**Features:** Adaptive Frequency Hopping

#### Scan Engine Options

Near/Far Area Imager (EX25)

#### Scan Range

##### Typical Reading Distances

Symbology	Density	Minimum Distance	Maximum Distance
Code 39	0.25 mm	16 cm	0.9 m
	10 mils	6.30 in	2.95 ft
	0.5 mm	18 cm	1.8 m
	20 mils	7.09 in	5.9 ft
	1 mm	18 cm	3.9 m
	40 mils	7.09 in*	12.8 ft
EAN 100%	1.4 mm	20 cm	4.8 m
	55 mils	7.87 in*	15.8 ft
	2.5 mm	20 cm	8.7 m
	100 mils	7.87 in*	28.5 ft
	8 mm	20 cm	17.8 m
	314 mils	7.87 in*	58.3 ft
DataMatrix	0.25 mm	20 cm	0.74 m
	10 mils	7.87 in*	2.43 ft
	1.4 mm	20 cm	3.4 m
	55 mils	7.87 in*	11.2 ft
	2.5 mm	20 cm	6.8 m
	100 mils	7.87 in*	22.3 ft

\* as long as the barcode label fits the reading area

#### Supported Bar Code Symbologies

Supports all popular symbologies including Australian Post, Aztec, BPO, Codabar, Codablock A and F, Code 11, Code 39, Code 93/93i, Code 128/ISBT 128/EAN 128, DataMatrix, Dutch Post, Canada Post, EAN.UCC composite, Interleaved 2 of 5, Japan Post, Matrix 2 of 5, MaxiCode, MSI Code, PDF417/MicroPDF417/MacroPDF417 (unbuffered mode), Planet, Plessey, Postnet, QR Code, RSS, Industrial and Standard 2 of 5, Telepen, TLC39, UPC/EAN/ISBN/ISSN/ISMN/GTIN processing

#### Environment

**Operating Temperature:** -20°C to +50°C (-4°F to +122°F)  
**Storage Temperature:** -20°C to +60°C (-4°F to +140°F)  
**Recharging Temperature:** 0°C to +35°C (32°F to +95°F)  
**Humidity:** 0 to 95% RH, Non-condensing  
**Shock and Vibration Protection:** SAE Specification J1399 Class 3 (off road vehicle)  
**Rain and Dust Resistance:** IP54  
**Drop Survival:** 26 drops onto concrete or steel surface from a height of 1.98 meters (6.5 feet)  
**Ambient light:** Works in any lighting conditions from 0 to 100,000 lux

#### Accessories

SR61 Dangle Suspension (wrist or fixed)  
 Belt Holster  
 Desktop / Wall Mount Charger  
 2, 4 and 8 Bay Charger  
 Bluetooth USB Adapter  
 Replacement Battery w/ Boot  
 EasySet™ Configuration Utility  
 Bluetooth RS232 adapter  
 Bluetooth USB adapter  
 Keypoint Bluetooth Software Wedge  
 Desktop Holder  
 Wall Mount Holder  
 Vehicle Holder

#### Regulatory Approvals

Laser Class 1 product; CISPR 22 Class B; Part 15 of FCC rules, Class B; CE Mark (EU) (EN 55024, EN 55022 Class B, IEC 60950-1, IEC 60825-1); cULus (Canada and the USA) (UL 60950-1); GS Mark (Germany) (EN 60950-1, EN 60825-1); NOM (Mexico); C-TICK (Australia and New Zealand) (AS/NZS 3548 based on CISPR22); CQC and SRRS (China); Spring Mark (Singapore); MIC (South Korea); ANATEL (Brazil)



#### North America

**Corporate Headquarters**  
 6001 36th Avenue West  
 Everett, Washington 98203  
 Phone: (425) 348-2600  
 Fax: (425) 355-9551

#### North Latin America

**Headquarters Office**  
 Mexico  
 Phone: +52 55 52-41-48-00  
 Fax: +52 55 52-11-81-21

#### South Latin America

**Headquarters Office**  
 Brazil  
 Phone: +55 11 5502.6770  
 Fax: +55 11 5502.6780

#### Europe/Middle East & Africa

**Headquarters Office**  
 Reading, United Kingdom  
 Phone: +44 118 923 0800  
 Fax: +44 118 923 0801

#### Asia Pacific

**Headquarters Office**  
 Singapore  
 Phone: +65 6303 2100  
 Fax: +65 6303 2199

#### Internet

www.intermec.com  
 Worldwide Locations:  
 www.intermec.com/locations

#### Sales

Toll Free NA: (800) 934-3163  
 Toll in NA: (425) 348-2726  
 Freephone ROW:  
 00 800 4488 8844  
 Toll ROW: +44 134 435 0296

#### OEM Sales

Phone: (425) 348-2762

#### Media Sales

Phone: (513) 874-5882

#### Customer Service and Support

Toll Free NA: (800) 755-5505  
 Toll in NA: (425) 356-1799

Copyright © 2010 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611841-01E 11/10

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

