



Symbol LS3578-FZ

Rugged, cordless scanner with integrated Bluetooth



FEATURES

High performance scanner with fuzzy logic decode capability

Quickly and accurately scans all 1D bar codes on the first scan, including poorly printed, dirty, damaged or low-contrast bar codes

Integrated Bluetooth Class 2 v1.2 (Serial Port and HID Profiles with authentication and security)

Cordless scanning with secure wireless data transmission

Cordless scanning

Enables real-time bar code data collection unrestricted by a cable, reducing repairs from cable failure

Ergonomic, rugged industrial design withstands up to 50 drops to concrete from 6.5 ft. (2m) and 2,500 3 ft. (1m) tumbles (5,000 hits)

Ensures maximum reliability with less downtime resulting from accidental drops

Accurately scan damaged or poorly printed bar codes

The Symbol LS3578-FZ cordless scanner provides fuzzy logic technology, enabling you to rapidly and accurately read damaged, dirty and poorly printed one-dimensional (1D) bar codes often found in industrial environments.

In the yard, warehouse, distribution center, manufacturing plant or retail store, the Symbol LS3578-FZ offers superior performance and reliability as well as a user-friendly form factor that helps ensure comfortable use over long shifts. Plus, integrated Bluetooth provides reliable and secure wireless data transmission between the scanner and host, including Motorola's rugged VC5090 Vehicle-Fixed Mount Mobile Computer.

Cordless freedom for improved productivity

With no cord between the scanner and host, employees can move freely throughout their work environment, increasing productivity and efficiency while keeping supply chain inventory up to date at all times. Plus, having no cord reduces downtime from cable breakdowns – a common point of failure in handheld devices used in industrial facilities.

Rugged design to maximize uptime

As rugged as it is innovative, the Symbol LS3578-FZ is designed for scan-intensive industrial applications

in the harshest operating conditions. Industry-leading impact tests ensure reliable performance in spite of the inevitable accidental drops. The device is impervious to dust and water, and its exit window is scratch-resistant and recessed for the highest level of durability. As a result, you avoid unnecessary equipment downtime or expensive equipment replacement costs.

Low total cost of ownership (TCO)

In addition to enhancing productivity, the LS3578-FZ offers a low TCO. The industrial-strength construction maximizes the scanner's working life, and multiple on-board interfaces provide true plug-and-play simplicity with your host system today and tomorrow. Support for Remote Scanner Management (RSM) enables you to discover, provision and upgrade devices from a central remote location, dramatically reducing management time and costs.

And since even the most rugged devices require a support plan, a full complement of Enterprise Mobility Services are available to help you protect your investment and maintain peak performance.

For more information, visit us at www.motorola.com/ls3578FZ or access our global contact directory at www.motorola.com/enterprisemobility/contactus.

SPECIFICATION SHEET

SYMBOL LS3578-FZ

Symbol LS3578-FZ Specifications

IP65-rated seal (electronic enclosure)

Protects against water and dust for reliable performance in the harshest environments

Bright LED and beeper with adjustable volume

Helps ensure that decode feedback is clearly visible and audible to users, even in noisy environments

Multi-point communication

Use up to three scanners with a single cradle, reducing capital expenditures and maintenance costs

Bright 650 nm laser aiming dot

Delivers clearly visible line for more accurate scanning

Supports GS1DataBar Symbologies (formerly RSS)

Ensures compatibility with emerging symbols to protect your hardware investment

Advanced data formatting

Eliminates costly modifications to the host software

Batch mode operation

Increases application design flexibility to better meet your specific needs

Remote scanner management ready

Enables you to discover, provision and upgrade devices from a central remote location, reducing management time and costs

| Physical Characteristics | |
|----------------------------------|--|
| Dimensions: | 7.34 in. L x 4.82 in. W x 2.93 in. D (18.65 cm H x 12.25 cm W x 7.43 cm D) |
| Weight: (including LiON battery) | 14.6 oz. (414 gm) |
| Battery: | 2200 mAh Lithium Ion Battery |
| Battery charge time: | Fully charged (100%) in 3 hours |
| Color: | Twilight Black and Yellow |

| Performance Characteristics | |
|-----------------------------|---|
| Scanner type: | Retrocollective |
| Light source: | 650 nm visible laser diode |
| Scan repetition: | 36 scans per second typical |
| Minimum element width: | 5 mil (0.127 mm) |
| Nominal working distance: | See decode zone |
| Print contrast: | 25% minimum reflective difference |
| Roll (Tilt) ¹ : | +/- 20 degrees from normal |
| Pitch ² : | +/- 65 degrees from normal |
| Skew (Yaw) ³ : | +/- 50 degrees from normal |
| Decode capability: | UPC.EAN, UPC.EAN with Supplemental, GS1-128 (formerly UCC/EAN 128), JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39 Trioptic, Code 128, Code 128 Full ASCII, Codabar (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, GS1DataBar (formerly RSS) |

| | |
|-----------------------|---|
| Interfaces supported: | RS232, Keyboard Wedge, IBM 468X/469X, USB and Synapse |
|-----------------------|---|

| User Environment | |
|--------------------------|---|
| Operating temperature: | -4° to 122°F (-20° to 50°C) |
| Storage temperature: | -40° to 140°F (-40° to 60°C) |
| Humidity: | 5% to 95% relative humidity, noncondensing |
| Sealing: | Sealed to IP65 specifications |
| Drop specifications: | Unit functions normally after 50 drops to concrete from 6.5 ft. (2m) |
| # of Cradle Insertions: | 250,000+ insertions |
| Ambient light immunity: | Immune to direct exposure of normal office and factory lighting conditions, as well as direct exposure to sunlight. |
| Electrostatic discharge: | Conforms to 20 kV air discharge and 8 kV of contact discharge |

| Cradles | STB 3508 and FLB 3508 | STB 3578 and FLB 3578 |
|-----------------------|--------------------------|--------------------------|
| Power requirements: | 4.75 – 14 VDC | 4.75 – 14 VDC |
| Typical current draw: | | |
| Not charging | 10 mA | 105 mA @5V 45 mA @9V |
| Fast rate charge | 915 mA @5V 660 mA @9V | 915 mA @5V 660 mA @9V |
| Slow rate charge | 480 mA @5V 345 mA @9V | 480 mA @5V 345 mA @9V |

| Radio specification | |
|---------------------|---|
| Radio: | Bluetooth, Class 2, Version 1.2, Serial port and HID Profiles 2.402 to 2.480 GHz adaptive frequency hopping (co-existence with 802.11 wireless networks) Data rate: 720 kbps Radio Range: Up to 300 ft. in open air* <small>* See Bluetooth Radio Performance Technical Brief for more information.</small> |

| Regulatory | |
|-----------------------------|--|
| Input transient protection: | IEC 1000-4-(2,3,4,5,6,11) |
| EMI/RFI: | FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Japan VCCI/MITI/Dentori |
| Laser safety: | IEC825-1 Class 2 |

| Warranty | |
|---|--|
| The Symbol LS3578-FZ is warranted against defects in workmanship and materials for a period of 3 years (36 months) from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions. See full warranty for details. | |

| Recommended Service | |
|---------------------------------|--|
| Service from the Start - Bronze | |

| Label Density | Depth of Field | |
|-------------------|----------------|-------------------|
| | LS3578-FZ | |
| Paper Label | English | Metric |
| Code 39 - 5 mil | 2.50" - 7.25" | 6.35 - 18.42 cm |
| Code 39 - 7.5 mil | 2.00" - 15.75" | 5.08 - 40.00 cm |
| 100% UPC - 13 mil | 1.00" - 24.00" | 2.54 - 60.96 cm |
| Code 39 - 20 mil | 0.00" - 39.50" | 0.00 - 100.33 cm |
| Code 39 - 40 mil | 2.00" - 67.00" | 5.08 - 170.18 cm |
| Code 39 - 55 mil | 4.00" - 84.00" | 10.16 - 213.36 cm |

For more detailed information, please see the Product Reference Guide in the Resource tab at www.motorola.com/ls3578fz



motorola.com

Part number SS-LS3578-FZ. Printed in USA 10/09. MOTOROLA and the Stylized M Logo and SYMBOL and the Stylized SYMBOL Logo are registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. ©2009 Motorola, Inc. All rights reserved. For system, product or services availability and specific information within your country, please contact your local Motorola office or Business Partner. Specifications are subject to change without notice.